

## **Double Disc Overseeder 1430A**

The Redexim Double Disc Overseeder has two rows of discs to cut grooves 30mm apart in the soil, seed is accurately delivered into the groove before the roller closes the groove to protect seed. With a single hopper & easy seed rate adjustment, the DD range is an obvious choice for operators.





| Specifications              |                 |
|-----------------------------|-----------------|
| SKU                         | 122.140.002     |
| Working width (m)           | 1.41            |
| Working width (inch)        | 55.5            |
| Max. Working depth (mm)     | 30              |
| Max. Working depth (inch)   | .19 - 1.18      |
| Max. Working speed (km h)   | 12              |
| Working speed (mph)         | 7.5             |
| Weight (kg)                 | 1340            |
| Weight (lbs)                | 2954            |
| Disc spacing (mm)           | 30              |
| Disc spacing (inch)         | 1.18            |
| Hopper capacity (Itr)       | 260             |
| Hopper capacity (cu.ft.)    | 9.18            |
| Number of seeding elements  | 47              |
| Min. Tractor HP required    | 40              |
| Min. lifting capacity (kg)  | 1340            |
| Max. capacity ( m² hr)      | 16920           |
| Max. capacity (ft² hr)      | 182125          |
| Three-point hitch           | 3-point CAT 1-2 |
| Lubricant                   | EP2             |
| Min. lifting capacity (lbs) | 2954            |