



CUSHMAN®

# SHUTTLE™ 2



## DELIVERS MORE THAN HARD WORK.

When you need to move large materials around your facility in a hurry, the Cushman® Shuttle™ 2 is the right choice. With a 1,200-pound cargo capacity and a 20.9-square-foot cargo deck, it can move anything from lumber to luggage. And whether it's equipped with a 48V DC electric drivetrain or a 13.5 hp Kawasaki® gas engine, the Shuttle 2 offers plenty of power to get the job done right.

**LET'S WORK.®**

**13.5HP**  
**KAWASAKI®**  
GAS ENGINE  
OPTION

**48V**  
**ELECTRIC**  
DRIVETRAIN  
OPTION

**20.9** SQ FT  
**CARGO DECK**  
CAPACITY



# CUSHMAN® SHUTTLE™ 2



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION  
STEERING

## OPTIONS & ACCESSORIES

- Drop Side Rails
- Locking Glove Box
- Rear View Mirror
- Windshield
- Canopy
- Front Disc Brakes
- Pin Stripes
- Body Color (Forest Green, White or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Beacon Light Kit
- Dome and Work Lights
- LED Headlights
- Hour Meter
- High Altitude Jetting
- Fuse Cab
- Steel Cab and Doors
- Defroster
- Wheel Covers - Spoke and Chrome
- Limited Slip Differential



COVERED WITH THE 2-YEAR CUSHMAN  
CARE TOTAL PROTECTION WARRANTY

### ELECTRIC MODEL

### GAS MODEL

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear)
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	141.0 in (358 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	4.3 in (11 cm) / 4.75 in (12 cm)
CARGO DECK CAPACITY	20.9 sq ft (1.94 m²) / N/A
POWER	
POWER SOURCE	48V DC / 4-Cycle, 24.5 ci (401cc) Low Emission
VALVE TRAIN	N/A / Single Cylinder OHV
HORSEPOWER (KW)	18.1 hp (13.5 kW) @ 1900 rpm / 13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	48V / Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Eight, 6V Deep Cycle / One, 12V Maintenance Free
BATTERY CHARGER	48 V, 120V AC, UL/CSA / N/A
KEY OR PEDAL START	Pedal
AIR CLEANER	N/A / Industrial Rated Dry Filter
LUBRICATION	N/A / Pressurized Oil System
OIL FILTER	N/A / Spin-On
COOLING SYSTEM	N/A / Air Cooled
FUEL CAPACITY	N/A / 6 Gallon (22.7 L) Tank
SPEED CONTROLLER	400 Amp Precision Drive System (PDS) / N/A
DRIVE TRAIN	Motor Shaft Direct Drive / Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse / Forward - Reverse
REAR AXLE RATIO	14.7:1 / 11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE	
SEATING CAPACITY	2-Person
WEIGHT W/O BATTERIES	810 lb (367 kg) / 926 lb (420 kg)
CURB WEIGHT	1300 lb (590 kg) / N/A
VEHICLE LOAD CAPACITY	1000 lb (454 kg) / 1200 lb (544 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m) / N/A
SPEED	13 mph ± 0.5 mph (21 kph ± 0.8kph) / 16 mph ± 0.5 mph (26 kph ± 0.8 kph)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	Links 18 x 8.5 - 8 (4 Ply Rated)

[www.cushman.com](http://www.cushman.com)

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82282-G3 (Rev. 01/2016)